

# Material Safety Data Sheet



## Section 1: Product and Company Identification

Product Name: **Bridge Deck Membrane Top Coat - Part B**

Sold By: **Bridge Preservation**  
**PO Box 10223**  
**Kansas City, MO 64171**  
**913.321.9006**

**FOR CHEMICAL EMERGENCY** Spill, leak, fire, exposure, or accident, call CHEMTREC day or night  
Domestic North America **800.424.9300** International **703.527.3887**

Fax Phone: **913.321.1490**

TSCA Inventory: All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL: All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

## Section 2: Composition/Information on Ingredients

<u>Hazardous Components</u>	<u>CAS#</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% by Wgt</u>
Tripropyleneglycoldiamine (MW>=2000)	9046-10-0			
Diethyltoluenediamine	68479-98-1			
Glycerine, propoxylated aminated (MW>=5000)	64852-22-8			

## Section 3: Hazards Identification

Emergency Overview:

Routes of Entry:	<u>Route</u>	<u>Entry Risk</u>
	<b>Inhalation</b>	Possible
	<b>Ingestion</b>	Possible
	<b>Skin Contact</b>	Possible
	<b>Eye Contact</b>	Possible

Potential Health Effects:	<b>Inhalation</b>	May cause nausea and respiratory tract irritation. May cause respiratory sensitization in susceptible individuals.
	<b>Ingestion</b>	Moderately toxic, cause abdominal cramps, nausea, swelling.
	<b>Skin Contact</b>	Product is a slight skin irritant. May Cause swelling and redness.
	<b>Eye Contact</b>	Mild eye irritant. Vapors slightly uncomfortable. Splashes irritating and painful.

Acute Health Hazards: Acute ingestion causes burning of the mouth, throat, and stomach with abdominal pain. Acute inhalation of vapors and mist can cause nasal discharge and pain in the eyes.

Chronic Health Hazards: If misted or at high concentrations, may cause pallor, nausea, anesthetic or narcotic effects.

Medical Conditions Generally Aggravated by Exposure: Skin and eye sensitization. Depending on individual skin sensitivity, chronic or prolonged exposure may result in irritation, blistering, burning and peeling of skin layers.

Carcinogenicity: OSHA: No data      ACGIH: No data      NTP: No data      IARC: No data  
Other:

## Section 4: First Aid Measures

Eye Contact:	Immediately flush with plenty of water for at least 15 minutes. If redness, itching, or a burning sensation develops, seek medical attention.
Skin Contact:	Remove from skin immediately. Rinse with clean water for 20-30 minutes. Use soapy water if needed. If redness, itching, or a burning sensation develops, seek medical attention.
Ingestion:	Do NOT induce vomiting! Dilute with water and seek medical attention immediately.
Inhalation:	Move victim to fresh air immediately. Give oxygen and seek medical attention.

## Section 5: Fire-Fighting Measures

Flammable Limits:	Class IIIB
Flash Point, (Method Used):	>200° Fahrenheit (Pensky Marten Closed)
Autoignition Temperature:	

NFPA Hazard Rating:	Health: 3	<b>Hazard Scale</b>	<b>Protective Equipment</b>
	Flammability: 1	0=LEAST	A=SAFETY GLASSES
	Reactivity: 0	1=SLIGHT	B=SAFETY GLASSES, GLOVES
	Other: B	2=MODERATE	C=SAFETY GLASSES, GLOVES AND APRON
		3=HIGH	D= SAFETY GLASSES, GLOVES , APRON and RESPIRATOR
		4=EXTREME	

HMIS Hazard Rating:	Health: 3
	Flammability: 1
	Reactivity: 0
	Protection: B

Extinguishing Media:	Foam/Carbon dioxide/Dry chemical/Water fog
Special Fire Fighting Procedures:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products exist.
Unusual Fire and Explosion Hazards:	Closed containers may rupture due to build-up of pressure when exposed to extreme heat.
Hazardous Decomposition Products:	

## Section 6: Accidental Release Measures

Accidental Release Measures:	Standard hydrocarbon spill procedures apply to this product.
------------------------------	--

## Section 7: Handling and Storage

Handling & Storage Precautions:	Prevent all skin and eye contact. Avoid breathing vapors. Re-seal partially used containers. Wash with soap and water before eating or drinking. Protect from moisture contamination. Exothermic generation of carbon dioxide may cause dangerous pressure. Keep away from all ignitable sources as well as extreme heat.
---------------------------------	---

## Section 8: Exposure Control/Personal Protection

Ventilation:	Adequate ventilation required. Local exhaust may be required in some areas. Special exhausting generally not required. Mechanical exhaust usually adequate.
Respiratory Protection:	Respiratory masks should be worn at all times when adequate ventilation does not exist. A NIOSH/MSHA respirator is acceptable.
Eye Protection:	Chemical tight goggles; full face shield if splashing is possible.
Skin Protection:	Coveralls and impervious foot covering is recommended.
Other Protective Clothing or Equipment:	Use impervious gloves, neoprene or rubber.

Work/ Hygienic Practices: Good air flow in working area. Eyewash station and safety shower should be available. Gloves and respiratory equipment should be worn at all times.

## Section 9: Physical and Chemical Properties

Appearance:	Gray or color of pigment additive		
Odor:	Slight ammonia odor		
Physical State:	Liquid		
ph As Supplied:	No Data		
ph (Other):	No Data		
Boiling Point:	>95° Fahrenheit		
Melting Point:	Not determined		
Freezing Point:	No Data		
Vapor Pressure (mmHg):	Not determined		
Vapor Density (Air=1):	Not determined		
Specific Gravity (Water=1):	1.01		
Evaporation Rate (Butyl Acetate=1):	Slower than		
Solubility in Water:	1-10%		
Percent Solids by Weight:	100%		
Percent Volatile (grams/liter):	By Weight: 0%	By Volume: 0%	
Volatile Organic Compounds (VOC) 9Grams/liter):	With Water: 0%	Without Water: 0%	
Viscosity:	No Data		

## Section 10: Stability and Reactivity

Stability:	Stable		
Conditions to Avoid ( <i>Stability</i> ):	Avoid excessive heat, open flam, sparks and strong oxidizing agents. Protect from atmospheric moisture. Replace outage with inert dry nitrogen.		
Incompatibility ( <i>Materials to Avoid</i> ):	Avoid strong oxidizers, acids.		
Hazardous Decomposition or Byproducts:	Carbon dioxide, carbon monoxide, nitrogen oxides.		
Hazardous Polymerization:	Will not occur under normal circumstances.		
Conditions to Avoid (Polymerization):	Avoid incompatible reactants, especially strong bases, water or temperatures over 160° Centigrade.		

## Section 11: Toxicological Information

Toxicological Information: No Data

## Section 12: Ecological Information

Ecological Information: No Data

## Section 13: Disposal Considerations

Waste Disposal Method:	Use excess product in an alternate beneficial application. Dispose of according to current local, state and federal regulations.
RCRA Hazard Class:	Non-Regulated



## Section 14: Transport Information

### U.S. Department of Transportation

Proper Shipping Name: Polyol Resin  
Hazard Class: Non-Regulated, NOI  
ID Number:  
Packing Group: III  
Label Statement:

### Water Transportation

Proper Shipping Name: Polyol Resin  
Hazard Class: Non-Regulated, NOI  
ID Number:  
Packing Group: III  
Label Statement:

### Air Transportation

Proper Shipping Name: Polyol Resin  
Hazard Class: Non-Regulated, NOI  
ID Number:  
Packing Group: III  
Label Statement:

### Other Agencies:

## Section 15: Regulatory Information

### U.S. Federal Regulations

- TSCA (Toxic Substance Control Act): Section 12(b) Export Notification. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States: There are no TSCA 12(b) Chemicals in this product.
- CERCLA (Comprehensive Response Compensation and Liability Act): CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product: Chemical Name- See Section 2
- SARA Title III (Superfund Amendments and Reauthorization Act): This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
- 311/312 Hazard Categories: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard: See Section 3
- 313 Reportable Ingredients: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: Chemical Name- See Section 2

### State Regulations:

California Proposition 65. The chemical(s) noted below and contained in this product are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at <0.1%. There are no proposition 65 chemicals known to exist in this product.

### International Regulations:

## Section 16: Other Information

Other Information:

Preparation Information:

Disclaimer:

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.