



# Bridge Deck Tack Coat

## PRODUCT DESCRIPTION

Bridge Deck Tack Coat is a specially formulated, high solids, single component, polymer modified bitumen primer designed to provide adhesion of asphalt overlays to Bridge Deck Membrane or Bridge Deck Membrane with an aggregated topcoat.

## USES

Bridge Deck Tack Coat may be used with all Bridge Deck Membrane coatings to promote adhesion between the Bridge Deck Membrane and asphalt wearing course overlays.

## PHYSICAL PROPERTIES

Color	Black
Specific Gravity @ 25°C	1.02
Boiling Point	N/A
Viscosity, 135°C, cps	650
Odor	Tar

## APPLICATION

Heat to 400°F for application. Apply by squeegee at a rate of 25 square feet per gallon. Cover Bridge Deck Membrane or aggregated topcoat at a rate of no less than 90%.

## PACKAGING

- Cardboard cartons at 50 pounds each.

## SHELF LIFE

One year, in original, unopened factory containers, under normal storage conditions of 55°F to 95°F.

## SAFETY

Keep away from open sparks or flame. Read Material Safety Data Sheet before using.

## WARRANTY

**Bridge Preservation** will refund the price of or replace, at its election, product it finds to be defective provided the product has been used properly. Except as expressly stated above, the Company makes no warranty of merchantability and no warranty of fitness for any particular purpose, nor does it make any warranty, expressed or implied, of any nature whatsoever with respect to the product or its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special or consequential damages, or for any charges or expenses of any nature incurred without its written consent.